

Uniclass L773			EPIC N57
CI/SfB			
	(66.3)	Xt6	1
20060384			

Issue Date: May 2010



Uni-8® Horizontal Lifeline® Cable Fall Protection System














working safely at heights

A workplace is considered to be at height if a person could be injured when falling from it, even if it is at or below ground level. This means that work place risks need to be carefully assessed and appropriate and proportionate control measures implemented in order to mitigate such risks. The Uni-8 Horizontal Lifeline System combined with good management controls provides a simple, yet comprehensive solution that will ensure compliance with current regulations in many circumstances.

The Uni-8 product is well suited to modern building projects, refurbishments and can also be used for a wide range of industrial safety applications.

The product is high quality, whilst providing excellent value for money. In typical

circumstances, the product can span up to 12m between support brackets. Uni-8 offers excellent functionality through it's free flowing bypass capability and can navigate corners and contours in building designs. Minimal moving parts and high grade materials ensure long life expectancy, low cost of ownership and add up to a sound investment. The system can be fitted to many types of structure and can also support multiple workers for both fall arrest and work restraint applications.

Detailed information to ensure safe system design and integration is provided by our comprehensive Uniline for Windows software programme and further enhanced by a comprehensive installation network.







working safely at heights features & benefits components

02

03

04

for more information about our range of equipment visit our website at www.unilinesafety.com







features & benefits

- high quality 316 stainless steel cable fall protection system offering excellent freedom of movement
- navigates corners and building contours
- in line energy absorbers protect buildings and structures
- spans of up to 12m (39.36ft) between intermediate supports
- electropolished components provide long-term corrosion resistance**

- a discreet and unobtrusive solution
- system performance calculated using bespoke design software
- conforms to EN795 Class C, OSHA 1915.159 & 1926.502M, ANSI Z359.1 2007 and AS/NZS 1891.2
- CE Marked

robust, functional cost effective

Unieye End Anchorage Connector – 316 Stainless Steel, electropolished, Serial Numbered – 67kN (14,773lbs) min breaking strength



Uni-8 System Tensioner – 316 stainless steel with anti-seizure tensioning unit and tension indicator disc



Uni-8 90 and 45 degree corners. 316 stainless steel, electropolished. Other angles achieved using variable bracket (Ul0404-VB)



C&G. U80405/0406/0407/041

^{**}some aggressive environments can cause corrosion and discolouration of stainless steel




8mm (5/16") 7x7 316 stainless steel cable – min breaking strength 38kn (8,542lbf).



Uni-8 intermediate bracket – 316 stainless steel, electropolished. Variable positioning available to suit a range of applications. Re-orientates load in the event of a fall.



Unigrab Attachment Device weighs only 0.29kg (0.64lbs) and fits in the palm of your hand. Can be attached at any point along the system. 316 stainless steel, electropolished and serial numbered.



- A Unieye (UE0100A)
- B 8mm Roll Swage 0.8kN Tensioner (U8T0400)* 8mm Hex Swage 0.8kN Tensioner (U8T0402) 8mm Swageless 0.8kN Tensioner (U8T0405)*
- **C** 8mm Tube Only 45° (U80406)
- **D** 7x7 8mm Stainless Steel Cable (U80800)
- E 8mm Intermediate Bracket (UI0404)
- F UniGrab (UG0800A)
- **G** 8mm Tube Only 90° (U80405)
- H 8mm Roll Swage Toggle (U8S0401)*
 8mm Hex Swage Toggle (U8S0403)
 8mm Swageless Toggle (U8S0406)*
- I Inline Energy Absorber (UA0600)
- J Wall Plate Anchor (UP0112A)

*This component is different from the one illustrated.
Fasteners for fixing to the structure are not supplied. For more detailed component information refer to the individual datasheets.

Uni-8 Swage Toggles – 316 Stainless Steel



Inline Force Management Energy Absorber – 316 Stainless Steel, electropolished



Wall Anchor Plate – 316 Stainless Steel, electropolished. 50kN min breaking strength



Capital Safety Group, through our Uniline brand is the global market leader in the design and manufacture of engineered fall protection systems. Through a combination of expert knowledge and practical experience, we can help our customers reduce risk and increase safety when working at height.

Our comprehensive Uniline range of products offers fully compliant, practical solutions for structures of all types, in all industries. Our ethos of delivering quality, service, training and support for our customers has earned Uniline a deserved reputation for excellence around the world.

Operating through specialist safety companies globally, Uniline provides local support and installation services to meet the specific safety objectives of all our customers.



If you need a safety solution for roof access during maintenance and inspection tasks, then look no further than Uniline's Roofing product range. Our products, including roof anchors, horizontal lifelines & horizontal rail systems offer comprehensive protection for workers on all types of roofs.



The products in our Horizontal systems range are some of the best know brands in fall protection safety. The versatility of these products combined with Uniline's expertise in fall protection ensures we can solve even the most complex of height safety problems in industry, construction, façade access and for all manner of building maintenance and inspection tasks.



vertical (systems™

The best vertical fall protection systems in the world won't let you down. The extensive development of this range of products for vertical structures including masts, towers, pylons, wind turbines, silos, bridges and chimney stacks ensures customers will enjoy the safest and most functional climbing experience possible.



A unique range of custom access products for challenging fall protection situations in transport and industry. These solutions are structurally analysed and designed to our customers exact needs and specifications.

local distributor/systems integrator

Worldwide Locations

UK

5a Merse Road North Moons Moat Redditch, Worcestershire B98 9HL

t: +44 (0) 1527 548 000 f: +44 (0) 1527 591 000

EUROPE, MIDDLE EAST & AFRICA

Le Broc Center Z.I. 1re Avenue – BP15 06511 Carros Le Broc Cedex FRANCE

t: +33 (0)4 97 10 00 10 f: +33 (0)4 93 08 79 70

USA

3833 SALA Way Red Wing MN 55066 USA

freephone: 800 328 6146 t: +1 (651) 388 8282 f: +1 (651) 388 5065

CANADA

260 Export Boulevard Mississauga Ontario L5S 1Y9 CANADA

freephone: 800 387 7484 t: +1 (905) 795 9333 f: 888 387 7484

AUSTRALIA & NEW ZEALAND

95 Derby Street Silverwater NSW 2128 AUSTRALIA

freephone: 1800 245 002 (AUS) freephone: 0800 212 505 (NZ) t: +61 2 8753 7600

ASIA

No 6 Tuas Avenue 18 638892 SINGAPORE

t: +(65) 65587758 f: +(65) 65587058











